



T8970

UNIVERSAL CONTINUOUS MEASUREMENT LEAK TESTER FOR THE GAS SECTOR



Continuous measurement for the gas sector.

T8970 is a particular leak testing equipment with continuous measurement, designed for specific parts with gas ramps, stoves or repair stations.

This technology will ensure very fast testing in sequence of the various rings and taps of a gas ramp, starting in automatic mode as soon as you connect to the inbound gas supply and displaying the leaks detected in real time.

The "volumetric measurement" function is standard, enabling display of the leak directly in cc/h or cc/min, to meet sector standards.

T8970 has an automatic electronic regulator, which enables stable and continuous adjustment of the test pressure, especially in the tap opening phase.

advanced measurement section in the world, thanks to the centring technology in windows and the double Faraday optical-isolated cage, which reduces the settling times under 18 ms.

This gives a real measurement resolution of 0.1 Pa at 1 bar, stable and noise-free.



6.2" colour display



Test graphic



Full area touch screen



Extended programming keyboard



Built-in processor and coprocessor



Centring technology in windows



Resolution from 0.1 Pa

Limitless connectivity.

T8970 equipment includes ports for the USB slave, RS232, RS485, Can bus, TTY, Profinet and EtherCAT. Assembly may also include an optional Ethernet port and a 26-pole connector with 4 inputs and 8 outputs, which are completely programmable, for interfacing with the external valves, safety barriers, switches, etc...

The front panel has a master USB port for connection to a USB key to save the tests conducted, backup/restore parameters and upgrade tool firmware.

The connection to thermal printers, barcode/data-matrix readers and markers takes place automatically using an internal menu.

Optimised pneumatic section.

Assembly of the latest generation valves has enabled a 30% increase in the filling speed compared to the previous model, maintaining the reliability unaltered over time. Our tools do not require expensive maintenance in the pneumatic department. Actually, our objective is to make them increasingly reliable and long-lasting.



Filling speed +30%



High strength against humidity



No periodic maintenance

Innovative design.

What appears to be a simple design exercise, in fact hides an in-depth study to make use and understanding of the equipment as simple as possible.

The front panel is made of a single sheet of tempered glass and aluminium, which makes it extremely easy to clean, making the T8970 suitable for use in the laboratory and on the production line.

The extensive internal menus are easy to understand and the graphic interface was designed to only display important information.

Everything is exactly where it should be.



Usb key



High power outputs



RS232, RS485, Can, TTY, Profinet, EtherCAT



Ethernet and auxiliary connector

Always better measurements.

The test cycle was further accelerated thanks to processor and coprocessor interaction, maintaining the reliability that has always made ForTest unique.

We can say with certainty that T8970 avails of the most



User-friendly interface



Easy to clean



Use in sectors at 360°



T8970

UNIVERSAL CONTINUOUS MEASUREMENT LEAK TESTER FOR THE GAS SECTOR



Application Sectors

Aerospace	Valves	Packaging
Automotive	Brakes	Gas
Household Appliances	Refrigeration	Heating
Electronics	Mechanical	Hydraulics
Foundry	Medical	Energy
Pneumatics	Oleodynamic	Cylinders

Measurement Characteristics

Type		Range from 0 to 1 bar
Δp(Leak)	Accuracy	0.5% RDS+3DGT
	Resolution	From 0.001 mbar to 0.1 mbar
Direct Pressure	Accuracy	0.5% FS

Optional

- Electronic regulator
- AUX I/O 24VDC with 8 output programmable, 4 input programmable, 4BCD
- Communication interfaces
- Pneumatic fast filling
- Pre-filling
- Volume measurement

Features

- Resolution from 0.1 Pa
- HMI touchscreen controller
- Colour display
- USB pen drive for store results and test parameters
- Bluetooth Low Energy and WiFi interfaces on-board
- Real Time Graph of pressure and decay
- 300 Test Programs
- USB Type-B female connector for PC
- 6 Languages (English, Italian, French, German, Spanish, Portuguese)
- Mechanical Start/Stop button
- Firmware upgrade via USB pen
- Password protection

- 24V I/O (Start,Stop,Filling,Test,Good,Reject,4BCD)
- Unit measure available: mbar, bar, psi, mmHg, mmH2O, Pa, HPa, cc/min, cc/h, pressure/s
- Frontal connector for Staubli calibrated leak

Technical Specifications

- Dimensions 270 × 160 × 300 mm
- Weight 8 Kg
- Electrical Supply 24VDC, 110 VAC, 230 VAC
- Air tube size: 4×2.7, 6×4, 8×6, 10×8

Test Modes

- Leak Test
- Obstruction

Communication Interfaces

Interface Name	Standard	Protocol
RS232/RS485	Yes	ForTest, Modbus RTU, Trace EOT
USB-Serial	Yes	ForTest, Modbus RTU, Trace EOT
Ethernet TCP/IP	Optional	ForTest, Modbus RTU, Trace EOT
Profinet	Optional	Profinet
EtherCAT	Optional	EtherCAT

Accessories

- Barcode reader
- Label printer
- Leak Test Manager PC software
- Air filter
- Electrovalve group "cylinder's" type with filter
- External Start/Stop push button